



DECLARATION OF PERFORMANCE

No

P054-5

version: 1

1 Unique identification code of the product-type: **Fundament 4,0 Szybki Profil SBS**

2 Intended use/es: damp proofing for buildings, including basement tanking

3 Manufacturer: Icopal Sp. z o.o., ul. Łaska 169/197,
98-220 Zduńska Wola, Polska (PL)

4 System/s of AVCP: System 2+, System 4

5 Harmonised standard: EN 13969:2004+A1:2006

Notified body/ies: The notified factory production control certification body No. 1488:
INSTYTUT TECHNIKI BUDOWLANEJ
(system 2+)

6 Declared performance/s:

Essential characteristics	Performances
Reaction to fire	NPD
Watertightness	200 kPa
Resistance to impact, method A	1500 mm
Resistance to impact, method B	2000 mm
Shear resistance of joints, side lap	800 +200/-100 N/50 mm
Shear resistance of joints, end lap	1000 +200/-100 N/50 mm
Flexibility at low temperatures (pliability)	-12 °C
Tensile strength longitudinal	950 +350/-0 N/50 mm
Tensile strength transverse	750 +350/-0 N/50 mm
Elongation longitudinal	50 ± 15 %
Elongation transverse	50 ± 15 %
Resistance to static load, method B	20 kg
Resistance to tearing longitudinal	350 ± 100 N
Resistance to tearing transverse	350 ± 100 N
Durability against artificial ageing/degradation: watertightness	200 kPa
Durability against chemicals: watertightness	NPD
Dangerous substances	not contain

NPD - No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

CZŁONEK ZARZĄDU
DYREKTOR
DS. TECHNICZNO PRODUKCYJNYCH

Grzegorz Hese

At Zduńska Wola on 16th February 2018